

# COMPLIANCE VS BEST PRACTICE 2 WAYS TO CLEAN A COOLING TOWER

## COMPLIANCE

### Standard Victorian Govt Regulated Clean

Complies with Vic Public Health & Wellbeing Act 2008

- Disinfection
- Cleaning
- Re-Disinfection



Basic report

(INDICATION ONLY)  
Labour to carry out:  
2 x 2m fiberglass Cng Tower  
1 man, 3 hours  
COST ESTIMATE \$200

## BEST PRACTICE

### Coolclean Standard Performance Clean

Complies with Vic Public Health & Wellbeing Act 2008

- Disinfection
- Cleaning
- Re-Disinfection



Complies with AS 3666.3 (Part 3)

- Clean, Inspection, Report



Complies with Manufacturers' Maintenance Instructions



**BONUS:** Remove/clean drift eliminators and clear water nozzles



Full report ([CLICK TO VIEW](#)) includes 4 photos

(INDICATION ONLY)  
Labour to carry out:  
2 x 2m fiberglass Cng Tower  
1 man, 6 hours  
COST ESTIMATE \$400

## BENEFITS

- Complies with Govt Regulations

- Complies with Govt Regulations & Manufacturer's Maint Instructions

- Controls legionella bacteria
- Water treatment is less complex
- Reduces breakdowns
- Performance gains, runs cooler

During a standard clean, Coolclean technicians check all components that can impact the performance, safety or compliance of the unit.

Many companies believe their cooling tower cleaning regime is sufficient, but it could be beneficial to use a more thorough, performance/safety-based service.



03 8765 9500



[www.coolclean.com.au](http://www.coolclean.com.au)